


# Spigots

- BFM® spigots are available in Stainless Steel T316L and T304L, as well as C22 Hastelloy.
- Available in a range of exact sizes, eliminating the imprecise nature of hose-clamp style connection widths and ensuring a perfect fit with the BFM® connector.
- All spigot diameters are measured at the base of the tail. The spigot design is slightly tapered, so the OD at the top of the tail is 5mm / 15/64" greater than the base
- BFM® spigots have a tail 52mm (2 3/4") long. These can be easily cut down or cut on an angle to suit your existing pipework.
- To enable the installation of a TR (Tool Release) connector, a 6mm / 15/64" hole is drilled in the top seat of the spigot head.



## Physical Properties

Material	Stainless Steel T316L Stainless Steel T304L or C22 Hastelloy (limited sizes)
Interior Finish	0.8Ra micro-metres (32Ra micro-inches)
Wall Thickness	Ø100mm/4" 1.5mm / 1/16" Ø125mm/5" upwards 2.0mm / 5/64"
Length	89mm / 3 1/2" (Head: 37mm / 1 1/2") (Tail: 52mm / 2 3/4")
Available Diameters (Stainless Steel Spigots)	100mm* / 4" 125mm / 5" 150mm / 6" then in 50mm/2" increments up to: 1,650mm / 65"
Available Diameters (Hastelloy Spigots)	150mm / 4" up to 500mm / 20" in 50mm / 2" increments

(\*measured externally (OD) - all other diameters measured internally (ID))

Note: For applications where there is a possibility for static build up, e.g. wood dust, flour, milk powder etc., we recommend using a static dissipative wire (strip), connecting the two BFM® spigots together.